



MATERIAL SAFETY DATA SHEET

DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Prepared: Jan. 29, 2007

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product: DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Chemical Family: Aromatic isocyanate

Product Use: Adhesive

Supplier: IFS Industries, Inc. 400 Orrton Avenue P.O. Box 1053 Reading, PA, USA 19603-1053

Telephone Number: 800 537 4502

In Emergency Only: CANUTEC Collect: (613) 996-6666 (24-hour hotline)
Information: (613) 992-4624 CHEMTREC 800 424 9300,

IFS Industries, Inc. EMERGENCY PHONE - (610) 378-1381 FAX (610) 378-5080

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview: Light brown, thick liquid. Sweet odour.
Toxic by inhalation.
Harmful if swallowed
May cause eye, skin, and/or respiratory tract irritation.

Potential Health Effects: Eyes - Irritant.

Skin - Irritant. Sensitizer. Prolonged/repeated contact can cause severe irritation.

Inhalation - Irritant. Sensitizer. May cause nausea and/or headaches. Persons with a history of respiratory problems should not be exposed to this product in a closed environment.

Ingestion - Will cause adverse health effects.

Chronic Effects - Prolonged or repeated inhalation of isocyanate vapours can be harmful.

SECTION 3: HAZARDOUS INGREDIENT INFORMATION

Ingredient %	(W/W)	CAS Number
Di-2-ethylhexyl phthalate	3 - 7	117-81-7

SECTION 4: FIRST AID MEASURES

Eyes: Flush open eyes with water for 15 minutes. Seek medical attention if irritation persists.

Skin: Remove affected clothing. Wash skin with soap and water immediately. Wash contaminated clothing before re-use. Seek medical attention if irritation persists.

Inhalation: Move to fresh air. Administer oxygen if necessary. Seek medical attention.

Ingestion: Seek medical attention immediately. Do not induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person.



MATERIAL SAFETY DATA SHEET

DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Prepared: Jan. 29, 2007

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Isolate from heat and open flame. Closed container may pressurize and explode when exposed to extreme heat. Material releases CO₂ on contamination with moisture, and may pressurize and explode.

Extinguishing Media: CO₂, chemical foam, dry chemical

Protection of Fire Fighters: Self contained breathing apparatus and full protective clothing should be worn by fire fighters.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment as recommended in Section 8.

Environmental Precautions: Obey relevant federal, provincial and municipal laws.

Methods for Containment: Cover spill with absorbent material. Place in an open-top container and remove to a ventilated area. Allow to sit in an open container for 24 hours.

Methods for Clean-Up: Decontaminate absorbent and spill area with a solution of 8% ammonia, 2% detergent and 90% water.

SECTION 7: HANDLING AND STORAGE

General Warning to Prevent Exposure:

Do not breathe fumes or vapours.
Avoid contact with eyes, skin, and clothing.
Wash thoroughly after handling.

General Storage Information:

Store in tightly-sealed containers in a cool, dry area.
Keep away from moisture.
Do not open containers until ready to use.
Inspect containers regularly to ensure that product is not building pressure.
If containers show signs of pressurization, place a tarpaulin over the container and relieve the pressure by puncturing the lid with a longhandled spike. (Only those required for this operation should be in the area.)

DURA PRO™

Adhesives & Coatings

MATERIAL SAFETY DATA SHEET

DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Prepared: Jan. 29, 2007

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingredient	Exposure Limit	Unit
Di-2-ethylhexyl phthalate	5 (TLV-TWA)	mg/m ³

Engineering Controls: Outdoor application: None required.
Indoor /enclosed areas: Use local exhaust ventilation to keep vapour concentrations below TLV.

Personal Protective Equipment:

Eyes: Safety glasses with side shields, or goggles.

Skin: Chemical-resistant rubber or plastic.

Inhalation: NIOSH-approved organic respirator if TLV is exceeded. (Respirator not required for outdoor applications.)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Thick, light-brown coloured liquid.

Odour: Sweet.

Melting Point: N/E

Boiling Point: N/E

Flash Point and Method: > 61°C

Evaporation Rate
(Butyl acetate = 1) N/E

Upper/Lower Flammable Limits: N/E

Vapour Pressure @ 77°F: N/E

Vapour Density: N/E

Specific Gravity @ 77°F: 1.26

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Moisture, excessive heat

Incompatible Materials: Water, strong bases, alcohols.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide will form at temperatures exceeding 500°F.

Possibility of Hazardous Reactions: Will not occur.



MATERIAL SAFETY DATA SHEET

DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Prepared: Jan. 29, 2007

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Dose Toxicity:

Di-2-ethylhexyl phthalate

Oral, LD50: 30000 mg/kg (rat)

Dermal, LD50: 25000 mg/kg (rabbit)

Inhalation, LC50: N/E

Repeated Dose Toxicity: N/E

Sensitization: May cause sensitization by skin contact or by inhalation.
May be an irritant to eyes, skin and/or lungs.

Carcinogenicity: N/E

Neurological Effects: N/E

Genetic Effects: N/E

Reproductive Effects: N/E

Developmental Effects: N/E

Target Organ Effects: Lungs chronic inhalation can cause respiratory distress and respiratory impairments

SECTION 12: ECOLOGICAL INFORMATION

Biodegradability Not readily biodegradable.

SECTION 13: DISPOSAL CONSIDERATIONS

Recover or recycle if possible.

Uncured product is hazardous waste. Incinerate in accordance with federal, state, and local environmental controls/regulations. Dispose of cured non-hazardous product in accordance with the same regulations.

All provided information only applies to the material as supplied to the user. The characteristics outlined may not apply if the material has been used or otherwise contaminated. It is the responsibility of the user to determine the proper waste identification and disposal methods in compliance with applicable regulations.

SECTION 14: TRANSPORT INFORMATION

NOT REGULATED FOR TRANSPORT



MATERIAL SAFETY DATA SHEET

DURA PRO™ PUR FLOOR® Moisture Cure Polyurethane Wood Floor Adhesive

Prepared: Jan. 29, 2007

SECTION 15: REGULATORY INFORMATION

US Regulations: All of the components of this material appear on the Toxic Substances Control Act (TSCA) inventory.
This product is not an OSHA-regulated material.

Canadian Regulations:

As per WHMIS, this material is classified as D2A (Other Material Causing Very Toxic Effects).

All of the components of this material appear on the Designated Substances List (DSL).

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all of the information required in the *Controlled Products Regulations*.

SECTION 16: OTHER INFORMATION

Abbreviations: N/E Not established

LIMITED WARRANTY

All statements, technical information, and recommendations set forth herein, are based on tests which IFS Industries, Inc. believes to be reliable. However, IFS Industries, Inc. does not guarantee their accuracy or completeness. The buyer should conduct his/her own test of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on IFS Industries, Inc.'s quotation. IFS INDUSTRIES, INC. DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL IFS INDUSTRIES, INC. BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and or patents covering any material or use.